

Linear Light L6 UGR<19 80 Series



General Description

TUBU's L6 Linear Sunlight s an All New Glare-free UGR<19, CRI80 linear fixture. It's perfect for office illumination. It's designed t distribute the light evenly across the floor glare-free in order to reduce stress on worker's eyes while maintaining a pleasant luminance in accordance with IEC62471. Powered by Samsung 3030 LEDs, high lumen up to 150lm/W and high CRI80. These lights offer a long lifetime and excellent lumen maintenance to minimise the maintenance costs.

Benefits

- Fast and easy installation
- A +++ 92% Energy saving compare to Halogen, 60% compare to Fluorescent, 60% compare to Metal Hilide lighting
- Lower maintenance cost thanks to over 3 times longer lifetime

Features

- Samsung 3030 LED's, up to 150lm/W
- Glare-free UGR<19, Provides Improved Visual Comfort
- High CRI >80
- SDCM<3
- TRIDONIC brand driver
- Flicker free
- Environmentally friendly, no mercury, No UV, No IR
- IP20, indoor use
- 5 Year Warranty on complete fixture. (LED's, Driver, & Housing)
- CE/RoHs certified

Applications

- Residential
- Healthcare
- Architectural
- Hospitality
- Retail

Electrical and Technical Data

Model No	TBL62F-20W80	TBL65F-50W80				
Input Power	20W	50W				
Dimension	600mm	1500mm				
Lumen	3000~3200lm	7500~7700lm				
Housing Color	White/Silver/Black					
ССТ	3000K/4000K					
CRI	>80					
SDCM	SDCM<3					
Power Factor	>0.9					
Driver	TRIDONIC Driver(Internal)					
IP Grade	IP20					
Input Voltage	220~240VAC					
Luminous Efficiency	150lm/W					
Beam Angle	40° & 60°					
Working Temp	-20°-45°					
Warranty	5 Years					
Lifespan	50,000Н					

Product Dimension&Package Details



Width: 50mm Height:70mm

Model	W(Norm)	H(Norm)	L(Norm)	N.W/CTN	G.W/CTN	Qty/CTN	Size/CTN
TBL62F-20W80	50mm	70mm	600mm	13KG	15.3KG	10PCS	630x285x385m
TBL65F-50W80	50mm	70mm	1500mm	15.5KG	18.5KG	4PCS	630x290x85m