

**flicker free / IP65 / IK10**

General Description

TUBU'S IP65 Easy-installation LED Tri-proof Light T1 are an ideal solution for both wet and dry locations such as parking garages and warehouses as well as factory production areas, basements and storage areas. They are available in lengths from 1200mm to 1500mm 40W/60W with both surface mount and suspended mount options.

Features

- IP65
- PC IK10
- System efficiency up to 130lm/W
- High CRI >80
- Linkable options with quick connection
- Environmentally friendly, no mercury, No UV, No IR
- Wide beam angle 120°
- Energy Efficiency Grade: A+
- Quick Start instant 100% luminous flux
- Flicker Free driver
- 5 Year Warranty on complete fixture. (LED's, Driver, & Housing)
- Certificate: CE, RoHS Certified
- Surface Mount or Suspended

Applications

- Car parking Lighting
- School Lighting
- Healthcare Lighting
- Workshops
- Supermark
- Warehouse
- Storage

Electrical and Technical Data

Model No	T1-SFN4F-40W	T1-SFN5F-60W
Input Power	40W	60W
Lumens	5200lm	7800lm
Lumen efficiency	130lm/W±5%	130lm/W±5%
Dimension	1200*69*78mm	1500*69*78mm
CCT	4000K & 5000K & 5700K	
CRI	>80	
Power Factor	>0.9	
IP Grade	IP65	
Input Voltage	AC200-240VAC (50/60Hz)	
Beam Angle	120°	
Working Temp	-40°~45° C	
Warranty	5 Years	
L90	>54,000hrs	

Product Dimension&Package Details

Model	L(Norm)	W(Norm)	H(Norm)	N.W/CTN	G.W/CTN	Qty/CTN	Size/CTN
T1-SFN4F-40W	1200mm	69mm	78mm	17.0KG	20.0KG	6PCS/CTN	1270*280*170mm
T1-SFN5F-60W	1500mm	69mm	78mm	18.0KG	22.0KG	6PCS/CTN	1570*280*170mm

Installation

Surface Mount



Suspension Mount

